


VBAPV & VBAPV-K



ALEV GECİKTİRİCİ ÖZELLİK/KÜÇÜK BÜKÜLME YARIÇAPI
FLAME RETARDANT CHARACTERISTIC/SMALL BENDING RADIUS



KULLANIM ALANLARI

- Bina içi tesisatlarda;
- Telefon santralleri ve abone dağıtımlarında
- Sinyal ve data iletiminde

KABLO YAPISI

1-İletken	IEC 60228; DIN VDE 0295; EN 60228 Sınıf 1 Elektrolitik Bakır
2-Yalıtım Direnci	PVC Kompaund
3-Yalıtım Renk	TS IEC 60189-2
4-Büküm	10 çiftte kadar katlar halinde 20 çift ~ 100 çift: 10 çiftli alt grupların birlikte bükümü; her grup polipropilen tanıtma şeridi ile sarılır
5-Ayırıcı Bant	Pes Bant (10 çift ve üstü)
6-Ekran	Kalaylı Bakır Toprak Teli + Pes Bant
7-Kılıf	PVC Kompaund
8-Kılıf Rengi	RAL 7001 Gri

APPLICATION

- At indoor installations;
- Telephone exchanges and subscriber distributions
- Signal and data transmission

CONSTRUCTION

1-Conductor	IEC 60228; DIN VDE 0295; EN 60228 Class 1 Electrolytic Copper
2-Insulation	PVC Compound
3-Colour Code	TS IEC 60189-2
4-Stranding	In layers up to 10 pairs 20 pairs - 100 pairs: 10 pair groups twisted together; each group is wrapped by polypropylene identification tape
5-Wrapping	Pes Tape (more than 10 pairs)
6-Screen	Tinned Copper Drain Wire + Pes Tape
7-Sheath	PVC Compound
8-Sheath Colour	RAL 7001 Grey

TEKNİK ÖZELLİKLER
TECHNICAL CHARACTERISTICS

İLETKEN DİRENCİ CONDUCTOR RES.	YALITIM DİRENCİ INSULATION RESISTANCE	EFEKTİF KAPASİTE MUTUAL CAPACITANCE	ÇALIŞMA SICAKLIĞI TEMPERATURE RANGE
mm Ω/km	500MΩxkm	120nF/km	-30°C - +70°C
0,5 97,8			
TEST VOLTAJ (AC) TEST VOLTAGE (AC)	ÇALIŞMA VOLTAJ OPERATING VOLTAGE	BÜKÜLME YARIÇAPI BENDING RADIUS	ALEV GECİKTİRİCİLİK TESTİ FLAME RETARDANT TEST
1000V	250V	8 x Cable Ø	IEC 60332-1-2 VDE 0482-332-1-2 EN 60332-1-2

NOTLAR
NOTES

VBV: Elektrolitik Bakır İletken
VBV-K: Kalaylı Bakır İletken
Esas alınan standartlar TS IEC 60189-2
VBAPV: Electrolytic Copper Conductor
VBAPV-K: Tinned Copper Conductor
Based on TS IEC 60189-2 standard

KOD NO CODE NR.		ÇİFT SAYISI VE İLETKEN ÇAPI (mm) NUMBER OF PAIRS AND WIRE DIAMETER (mm)	KABLO ÇAPI (mm) OVERALL DIAMETER (mm)	BAKIR AĞIRLIĞI (kg/km) COPPER WEIGHT (kg/km)	YAKLAŞIK KABLO AĞIRLIĞI (kg/km) APPROX. CABLE WEIGHT (kg/km)	STANDART UZUNLUK (mt) STANDARD LENGTH (m)
VBAPV	VBAPV-K					
342405012	342505012	1 x 2 x 0,50	3,30	7	23	100/500/1000
342405022	342505022	2 x 2 x 0,50	4,30	13	29	100/500/1000
342405032	342505032	3 x 2 x 0,50	4,60	15	39	100/500/1000
342405042	342505042	4 x 2 x 0,50	4,80	19	44	100/500/1000
342405052	342505052	5 x 2 x 0,50	5,20	22	52	100/500/1000
342405062	342505062	6 x 2 x 0,50	5,60	26	59	100/500/1000
342405102	342505102	10 x 2 x 0,50	7,40	40	93	100/500/1000
342405202	342505202	20 x 2 x 0,50	9,20	77	147	100/500/1000
342405302	342505302	30 x 2 x 0,50	10,70	110	205	100/500/1000
342405502	342505502	50 x 2 x 0,50	13,40	180	314	100/500/1000
342405112	342505112	100 x 2 x 0,50	19,00	365	600	100/500/1000
342405222	342505222	200 x 2 x 0,50	26,00	725	1140	100/500